HSF RoHS cULus CE

REVISION RECORD				
REV	ECN	DESCRIPTION	DRFT	DATE
A0		NEW		21.10.08

SPECIFICATIONS
Rated(**额定参数**)：300V,8A
Dielectric strength(**抗电强度**)：AC1500V/1 Minute
Insulation Resistance(**绝缘电阻**):1000MΩ Min
Contact Resistance(**接触电阻**):20mΩ Max
Screw Torque(**扭矩**)：0.2Nm（1.7Lb.in）
Wire Range(**线径**):28~16AWG
Strip length(**剥线长度**):6-7mm
Temp. range(**操作温度**)：-40℃~+105℃
MAX Soldering(**瞬时温度**):+250°C,5s


Housing Material(**塑件**)：PA66（UL94 V-0）
Contact(**端子**)：Phosphor Bronze，Tin plating(**磷铜镀镍**)
Clamp(**方块**)：Brass(**黄铜**)，Ni plating(**镀镍**)
Screw（**螺丝**)：M2.0 Steel，Zinc plating(**钢,镀锌**)


PITCH RANGE IN MM			NOMINAL DIMENSION RANGE IN MM				
TO 6	OVER 6 TO 10	OVER 10 TO 24	TO 30	OVER 30 TO 60	OVER 60 TO 100	OVER 100 TO 150	OVER 150
±0.10	±0.15	±0.25	±0.30	±0.30	±0.50	±0.70	±1.00


Ordering Information


WFD15EDGK-508 XX G 0 1

- Pitch: 508=5.08PH
- No.of pins: 2P,3P,4P~16P
- Housing Color: B=Black, G=Green, U=Blue, R=Red, W=White, Y=Yellow, O=Orange, E=Grey
- Packing: 0=Pe bag, A=Tray









DRAW	LIU MIAO	SCALE	FIT
		UNIT	mm
CHECK		SIZE	A4
		SHEET	1/1
APPROVE		PROJ.	

WFDCONN 深圳市旺富达电子有限公司 SHEN ZHEN WFD ELECTRONICS CO., LTD

PART NO.	WFD15EDGK-508XXG01
TITLE:	15EDGK-5.08-XXP插拔式母座/绿色