HSF RoHS cULus CE

NOTES1:

UL Standard

1.Rated voltage/current : 300V / 20A
3.Torque value : M2.5 , 3.5Lb.in
4.Wire range : 30~12AWG

IEC Standard

1.Rated voltage/current : 450V / 24A
2.Torque value : M2.5 , 0.4N·m
3.Wire range : 0.5~2.5mm²


NOTES2:


1.Dimension shall be interpreted per ASME Y14.5-2009
2.Pitch : 7.50mm, Poles : N=02~16P
3.Stripping length : 12~13mm
4.Withstanding voltage : AC2500V/1Min
5.Operating temperature: -40°C~+105°C
6.Undimensioned tolerances:


Pitch range in mm			Nominal dimension range in mm					— ⌒ ▱
TO 6	Over 6 TO 10	Over 10 TO 24	TO 30	Over 30 TO 60	Over 60 TO 100	Over 100 TO 150	Over 150	0.1/10
								∠
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2°


7.RoHS Compliance

REVISION RECORD				
REV	ECN	DESCRIPTION	DRFT	DATE
A0		NEW		21.08.16










Ordering Information

WFD105R-750XXG01

- 750 — Pitch: 750=7.5PH
- XX — No.of pins: 2P~24P
- G — Housing Color: B=Black, G=Green, U=Blue, R=Red, W=White, Y=Yellow, O=Orange, E=Grey
- 01 — Packing: 0=Pe bag, T=Tube, A=Tray



DRAW	Liu Miao	SCALE	FIT
		UNIT	mm
CHECK	SIMON	SIZE	A4
		SHEET	1/1
APPROVE	DAVID	PROJ.	

WFD CONN 深圳市旺富达电子有限公司 SHEN ZHEN WFD ELECTRONICS CO., LTD

PART NO.	WFD105R-750XXG01
TITLE:	105R-7.5-XXP螺钉式/弯脚/绿色