HSF RoHS cULus CE

REVISION RECORD				
REV	ECN	DESCRIPTION	DRFT	DATE
A0		NEW		21.07.10

SPECIFICATIONS

Rated(**额定参数**)：150V,10A

Dielectric strength(**抗电强度**)：AC1500V/1 Minute

Insulation Resistance(**绝缘电阻**):1000MΩ Min

Contact Resistance(**接触电阻**):20mΩ Max

Screw Torque(**扭矩**)：0.2Nm（1.7Lb.in）

Wire Range(**线径**):26~16AWG

Strip length(**剥线长度**):5-6mm

Temp. range(**操作温度**)：-40℃~+105℃

MAX Soldering(**瞬时温度**):+250°C,5s

Housing Material(**塑件**)：PA66（UL94 V-0)

Contact(**端子**)：Brass，Tin plating(**黄铜镀锡**)

Wire protector(**弹片**)：Brass(**黄铜**)，Ni plating(**镀镍**)


Screw（**螺丝**)：M2.0，Steel，Zinc plating(**钢,镀锌**)


PITCH RANGE IN MM			NOMINAL DIMENSION RANGE IN MM				
TO 6	OVER 6 TO 10	OVER 10 TO 24	TO 30	OVER 30 TO 60	OVER 60 TO 100	OVER 100 TO 150	OVER 150
±0.10	±0.15	±0.25	±0.30	±0.30	±0.50	±0.70	±1.00


Ordering Information


WFD124D - 350 XX G 0 1


- 350 — Pitch: 350=3.50PH
- XX — No.of pins: 2P,3P,4P~24P
- G — Housing Color: B=Black, G=Green, U=Blue, R=Red, W=White, Y=Yellow, O=Orange, E=Grey
- 0 — Packing: 0=Pe bag, T=Tube, A=Tray
- 1











Recommended P.C.B Layout(Top Side)

DRAW	Liu Miao	SCALE	FIT
		UNIT	mm
CHECK	SIMON	SIZE	A4
		SHEET	1/1
APPROVE	DAVID	PROJ.	

WFD CONN 深圳市旺富达电子有限公司 SHEN ZHEN WFD ELECTRONICS CO., LTD

PART NO.	WFD124D-350XXG01
TITLE:	124D-3.5-XXP螺钉式端子台/绿色