HSF RoHS cULus CE

REVISION RECORD				
REV	ECN	DESCRIPTION	DRFT	DATE
A0		NEW		21.6.26

NOTES1:

UL Standard

1.Rated voltage/current : 300V / 30A
2.Withstanding voltage : AC3000V/1Min.
3.Torque value : M3 , 4.4Lb.in
4.Wire range : 26~10AWG

IEC Standard

1.

Pollution degree	2
Overvoltage category	Ⅲ
Rate impulse voltage(KV)	3.5KV
Rate voltage(V)	1000V
Rate current(A)	32A

2.Torque value : M3 , 0.5N·m
3.Wire range : 0.2~6.0mm²

NOTES2:

1.Dimension shall be interpreted per ASME Y14.5-2009
2.Pitch : 9.52mm, Poles : N=02~24P
3.Stripping length : 8-9mm
4.Operating temperature: -40℃~+105℃
5.Undimensioned tolerances:


Pitch range in mm			Nominal dimension range in mm						— ⌒ ▱
TO 6	Over 6 TO 10	Over 10 TO 24	TO 30	Over 30 TO 60	Over 60 TO 100	Over 100 TO 150	Over 150		0.1/10
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30		±2°


6.RoHS Compliance

Ordering Information


WFD636 - 952 XX G 01


- Pitch: 952=9.52PH
- No.of pins: 2P,3P,4P~24P
- Housing Color: B=Black, G=Green, U=Blue, R=Red, W=White, Y=Yellow, O=Orange, E=Grey
- Packing: 0=Pe bag, T=Tube, A=Tray





Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)





DRAW	Liu Miao	SCALE	FIT
		UNIT	mm
CHECK	SIMON	SIZE	A4
		SHEET	1/1
APPROVE	DAVID	PROJ.	

WFD CONN 深圳市旺富达电子有限公司 SHEN ZHEN WFD ELECTRONICS CO., LTD

PART NO.	WFD636-952XXG01
TITLE:	636-9.52-XXP螺钉式/绿色