


HSF RoHS

SPECIFICATIONS
PERFORMANCE

Electical Rating:AC/DC 50V 0.5A
Insulation Resistance: 500MΩ Min
Contact Resistance:50mΩ Max
Withstang Volt:150V AC/minute
Opratng Temperature:−40°C to +105°C
Material
Contact:Phosphor Bronze
Housing:LCP UL94V0
Max.Processing Temp:230°C for30−60 seconds
(260°C for 10 seconds)








Ordering Information

3712 F 064 103 XX F X 0X

No.of Pins	Piastics Height	Contact Plating	Insulator Material	Packing
64P	H=10.3	G0:Gold Flash G4:3U" Gold G5:5U" Gold G6:10U" Gold G7:15U" Gold S0:Gold Flash/Tin SN:Tin	Option F=LCP	R=Tape&Reel P=Tube+Cap



RECOMMEND P.C.BOARD LAYOUT
PCB TOLERANCE:±0.05

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2016.07.30	NEW DRAWING	

OPERATION		DRAW	LIU MIAO	16.07.30	SCALE	FIT
X.X	±0.30				UNIT	mm
X.XX	±0.20	CHECK			SIZE	A4
X.XXX	±0.10				SHEET	1/1
Angle	±3°	APPROVE			PROJ.	
DIM	TOL					

WFDCONN 深圳市旺富达电子有限公司
SHEN ZHEN WFD ELECTRONICS CO., LTD

PART NO.	3712F064103XXFX0X
TITLE:	1.0BTB-64PIN H=10.3母头 带夹持盖