
零件名称	零件料号	用量
针管	GP6283-0101	1 PCS
针头	TH0014-0101	1 PCS
弹簧	SA6267	1 PCS

序号	更改内容及描述	更改人	日期



NOTE

1.Material
Plunger: Brass C6801
Barrel: Brass C6801
Spring: SUS 304

2.Plating
Plunger: 1 micro-inch minimum Au over 50~100 micro-inch nickel
Barrel: 1 micro-inch minimum Au over 50~100 micro-inch nickel

3.Electrical
Rated current & voltage: DC 12V; 1.0A Max.
Contact resistance: 50 mohm maximum at normal working height(quiescence)

4.Mechanic
Spring force: 50g-80g at normal working height
Durability: 10,000 cycles(minimum)

5.To ensure the best usage,please operate it based on the working height
Based on the engineering drawings,shall not exceed the maximum allowed compression

6.To avoid arcing issue, The adaptor start to power supply after connector mated fully.

7.RoHS compliant product.

WFD CONN 深圳市旺富达电子有限公司
SHEN ZHEN WFD ELECTRONICS CO., LTD

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X.X ±0.15 X.XX ±0.10 X.XXX ANG. ±2°	APPROVED BY	DATE	TITLE: POGO PIN	
	CHECKED BY	DATE		
	DRAWN BY: Liu Miao	DATE: 2022/06/05	DOCUMENT NO: DNOXX-00X	PAGE: 1
UNIT: mm	SIZE: A4	PART NO: PGC-9.3-1PIN	REV: A	SHEET: 1/1 SCALE: 1:1