
HSF RoHS


FILE NO :E362810

SPECIFICATIONS
Rated Current:3.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:1000V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°c to +105°c

Contact Material:Brass
Contact Plating:Au or Sn Over Ni
Insulator Material:Polyester(UL94V−0)
Standard: PA6T
Max.Processing Temp: 230°C for 30−60 seconds
(260°C for 10 seconds)




Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)




Ordering Information

1215-1 2 XX X N XX R XXX X 01

No.of Pins Per Row 1x40 2x40 3x40 1--40 2--80 3--120	Insulator Material Option A=BK−PBT B=BK−PA66 C=BK−PA6T D=BK−PA46 F=BK−LCP	Contact Plating G0:Gold Flash G2:5U" Gold G3:10U" Gold G4:15U" Gold G5:30U" Gold S0:Gold Flash/Tin SN:Tin	Pin Length	Packing 0=PE Bag A=Tray T=Tube	





Dimension antitheses list				
ITEM	PA	PB	PC	L
Standard	6.00	6.90	3.00	13.8/18.8
Alternate				

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2012.04.11	NEW DRAWING	

OPERATION		DRAW	Liu Miao	12.04.11
X.X	±0.30			
X.XX	±0.20	CHECK		
X.XXX	±0.10			
Angle	±3°	APPROVE		
DIM	TOL			

SCALE	FIT
UNIT	mm
SIZE	A4
SHEET	1/1
PROJ.	

WFD CONN 深圳市旺富达电子有限公司
SHEN ZHEN WFD ELECTRONICS CO., LTD

PART NO.	121512XXXNXXRXXXX01
TITLE:	2.54xH1.5mm Pin Header Dual Row 90°