
HSF RoHS


FILE NO :E362810


SPECIFICATIONS
Rated Current:3.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:1000V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°c to +105°c


Contact Material:Brass
Contact Plating:Au Over Ni
Insulator Material:Polyester(UL94V−0)
Standard: PA6T
Max.Processing Temp: 230°C for 30−60 seconds
(260°C for 10 seconds)



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)







Ordering Information

1217 11 XX X N XX R XXX X 01

No.of Pins Per Row 1x40 1−−40	Insulator Material Option	Contact Plating	Pin Length	Packing
	A=BK−PBT	G0:Gold Flash		0=PE Bag
	B=BK−PA66	G2:5U" Gold		T=Tube
	C=BK−PA6T	G3:10U" Gold		A=Tray
	D=BK−PA46	G4:15U" Gold		
	F=BK−LCP	G5:30U" Gold		
		S0:Gold Flash/Tin		
		SN:Tin		

Dimension antitheses list				
ITEM	PA	PB	PC	L
Standard	6.00	3.50	3.00	13.10
Alternate				

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2014.02.03	NEW DRAWING	

OPERATION		DRAW	Liu Miao	14.02.03
X.X	±0.30			
X.XX	±0.20	CHECK		
X.XXX	±0.10			
Angle	±3°	APPROVE		
DIM	TOL			

SCALE	FIT
UNIT	mm
SIZE	A4
SHEET	1/1
PROJ.	

WFD CONN 深圳市旺富达电子有限公司
SHEN ZHEN WFD ELECTRONICS CO., LTD

PART NO.	121711XXXNXXRXXXX01
TITLE:	2.54mm Pin Header 1.7mm Single 90°