

HSF RoHS FILE NO :E362810


SPECIFICATIONS
Rated Current:3.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:1000V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°c to +105°c


Contact Material:Brass
Contact Plating:Au or Sn Over Ni
Insulator Material:Polyester(UL94V−0)
Standard: PA6T
Max.Processing Temp: 230°C for 30−60 seconds
(260°C for 10 seconds)

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)









Ordering Information

1274-12 XX X N XX R XXX X01

No.of Pins Per Row	Insulator Material Option	Contact Plating	Pin Length	Packing
2x40 2−−80	A=BK−PBT B=BK−PA66 C=BK−PA6T D=BK−PA46 E=BK−PA9T F=BK−LCP	G0:Gold Flash G1:3U" Gold G2:5U" Gold G3:10U" Gold G4:15U" Gold G5:30U" Gold S0:Gold Flash/Tin SN:Tin		**0=PE Bag** **A=Tray** **T=Tube** **P=Tube+Cap** **R=Reel+Cap**

Dimension antitheses list

ITEM	PA	PC	L短	L长
Standard	6.00	3.60	15.30	20.30

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2018.11.11	NEW DRAWING	

OPERATION		DRAW	Liu Miao	18.11.11	SCALE	FIT
X.X	±0.30				UNIT	mm
X.XX	±0.20	CHECK			SIZE	A4
X.XXX	±0.10				SHEET	1/1
Angle	±3°	APPROVE			PROJ.	
DIM	TOL					

WFD CONN 深圳市旺富达电子有限公司
SHEN ZHEN WFD ELECTRONICS CO., LTD

PART NO.	127412XXXNXXRXXXX01
TITLE:	2.54PH 2xNpin H7.40mm 90°