

HSF RoHS FILE NO :E362810


SPECIFICATIONS
Rated Current:3.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:1000V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°c to +105°c

Contact Material:Brass
Contact Plating:Au Over Ni
Insulator Material:Polyester(UL94V−0)
Standard: PA6T
Max.Processing Temp: 230°C for 30−60 seconds
(260°C for 10 seconds)





Type01






Type02







Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)

Ordering Information

1215 2 1 XX X N XX M XXX X 01(2)

No.of Pins Per Row 1*40	Insulator Material Option	Post	Contact Plating		Pin Length	Packing
	A=BK−PBT	W=With Post	G0:Gold Flash			0=PE Bag
	B=BK−PA66	N=W/O Post	G2:5U" Gold			A=Tray
	C=BK−PA6T		G3:10U" Gold			T=Tube
	D=BK−PA46		G4:15U" Gold			P=Tube+Cap
	F=BK−LCP		G5:30U" Gold			R=Reel+Cap
			S0:Gold Flash/Tin			M=Reel+Mylar
			SN:Tin			

Dimension antitheses list					
ITEM	PA	D	PB	W	L
Standard	6.00	0.20	4.00	5.00	11.80
Alternate					

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2013.03.28	NEW DRAWING	

OPERATION	
X.X	±0.30
X.XX	±0.20
X.XXX	±0.10
Angle	±3°
DIM	TOL

DRAW	Liu Miao	13.03.28
CHECK		
APPROVE		

SCALE	FIT
UNIT	mm
SIZE	A4
SHEET	1/1
PROJ.	

WFD CONN 深圳市旺富达电子有限公司
SHEN ZHEN WFD ELECTRONICS CO., LTD

PART NO.	121521XXXNXXMXXXX01(2)
TITLE:	2.54mm Pin Header H1.5+1.5mm SMT