
HSF RoHS


FILE NO :E362810

SPECIFICATIONS
Rated Current:3.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:1000V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°C to +105°C

Contact Material:Brass
Contact Plating:Au or Sn Over Ni
Insulator Material:Polyester(UL94V−0)
Standard: PA6T
Max.Processing Temp: 230°C for 30−60 seconds
(260°C for 5 seconds)




Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)




Ordering Information

1217 1 2 XX X N XX M XXX X 01

No.of Pins	Insulator Material Option	Post	Contact Plating	Pin Length	Packing
Per Row 2*2~2*40	A=BK−PBT C=BK−PA6T E=BK−PA9T F=BK−LCP	W=With Post N=W/O Post	G0:Gold Flash G1:3U" Gold G2:5U" Gold G3:10U" Gold G4:15U" Gold G5:30U" Gold S0:Gold Flash/Tin SN:Tin		0=PE Bag A=Tray T=Tube P=Tube+Cap R=Reel+Cap M=Reel+Mylar





Dimension antitheses list				
ITEM	PA	PB	W	L
Standard	6.00	2.50	7.50	10.3
Alternate				

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2020.02.22	NEW DRAWING	

OPERATION	
X.X	±0.30
X.XX	±0.20
X.XXX	±0.10
Angle	±3°
DIM	TOL

DRAW	Liu Miao	20.02.22
CHECK		
APPROVE		

SCALE	FIT
UNIT	mm
SIZE	A4
SHEET	1/1
PROJ.	

WFD CONN 深圳市旺富达电子有限公司
SHEN ZHEN WFD ELECTRONICS CO., LTD

PART NO.	121712XXXNXXMXXXX01
TITLE:	2.54PH 2xNpin H1.7mm SMT