

HSF RoHS FILE NO :E362810


SPECIFICATIONS
Rated Current:3.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:1000V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°c to +105°c


Contact Material:Brass
Contact Plating:Au Over Ni
Insulator Material:Polyester(UL94V−0)
Standard: PA6T
Max.Processing Temp: 230°C for 30−60 seconds
(260°C for 10 seconds)



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)







Ordering Information

1225 12 XX X N XX Z XXX X 0X

No.of Pins Per Row	Insulator Material Option	Contact Plating	Pin Length	Packing
2~40	A=BK−PBT C=BK−PA6T D=BK−PA46 E=BK−PA9T F=BK−LCP	G0:Gold Flash G1:1U" Gold G2:1.5U" Gold G3:2U" Gold G4:3U" Gold G5:5U" Gold G6:10U" Gold G7:15U" Gold S0:Gold Flash/Tin SN:Tin		0=PE Bag A=Tray T=Tube P=Tube+Cap R=Reel+Cap M=Reel+Mylar

Dimension antitheses list

ITEM	PA	A	PC	L短	L长
Standard	6.00	3.94	8.50	12.50	18.50

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2019.09.21	NEW DRAWING	

OPERATION	
X.X	±0.30
X.XX	±0.20
X.XXX	±0.10
Angle	±3°
DIM	TOL

DRAW	Liu Miao	19.09.21
CHECK		
APPROVE		

SCALE	FIT
UNIT	mm
SIZE	A4
SHEET	1/1
PROJ.	

WFD CONN 深圳市旺富达电子有限公司
SHEN ZHEN WFD ELECTRONICS CO., LTD

PART NO.	122512XXXNXXZXXXX0X
TITLE:	2.54PH H2.5mm Dual Row 卧贴加盖