
HSF RoHS


FILE NO :E362810


SPECIFICATIONS
Rated Current:1.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:500V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°C to +105°C


Contact Material:Phoshpor Bronze
Contact Plating:Au or Sn Over Ni
Insulator Material:Polyester(UL94V−0)
Standard: PA6T
Max.Processing Temp: 230°C for 30−60 seconds
(260°C for 10 seconds)

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE± 0.05)









Ordering Information

2434 01 XX X N XX S U X 0X

- No.of Pins 2~50
- Insulator Material Option
  - C=BK−PA6T
  - E=BK−PA9T
  - F=BK−LCP
- Contact Plating
  - G1:Gold Flash
  - G3:2U" Gold
  - G4:3U" Gold
  - G5:5U" Gold
  - G6:10U" Gold
  - G7:15U" Gold
  - S0:Gold Flash/Tin
  - SN:Tin
- Packing
  - A=Tray
  - T=Tube
  - P=Tube+Cap
  - R=Reel+Cap

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2019.03.28	NEW DRAWING	

OPERATION		DRAW	Liu Miao	19.03.28	SCALE	FIT
X.X	±0.30				UNIT	mm
X.XX	±0.20	CHECK			SIZE	A4
X.XXX	±0.10				SHEET	1/1
Angle	±3°	APPROVE			PROJ.	
DIM	TOL					

WFD CONN 深圳市旺富达电子有限公司
SHEN ZHEN WFD ELECTRONICS CO., LTD

PART NO.	243401XXXNXXSUX0X
TITLE:	1.27PF H3.4mm 1xNpin 180° W1.8