

HSF RoHS FILE NO :E362810


SPECIFICATIONS
Rated Current:1.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:500V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°c to +105°c


Contact Material:Phosphor Bronze
Contact Plating:Au Over Ni
Insulator Material:Polyester(UL94V−0)
Standard: PA6T
Max.Processing Temp: 230°C for 30−60 seconds
(260°C for 10 seconds)



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)







Ordering Information

2443 01 XX X N XX R U X 0X

No.of Pins Per Row	Insulator Material Option	Contact Plating		Packing		Stream code
2~50	A=BK−PBT	G1:Gold Flash		0=PE Bag		01~99
	C=BK−PA6T	G3:2U" Gold		A=Tray		
	D=BK−PA46	G4:3U" Gold		T=Tube		
	E=BK−PA9T	G5:5U" Gold		R=Reel		
	F=BK−LCP	S0:Gold Flash/Tin				
		SN:Tin				

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2012.04.18	NEW DRAWING	

OPERATION		DRAW	Liu Miao	2012.04.18	SCALE	FIT
X.X	±0.30				UNIT	mm
X.XX	±0.20	CHECK			SIZE	A4
X.XXX	±0.10				SHEET	1/1
Angle	±3°	APPROVE			PROJ.	
DIM	TOL					

WFD CONN 深圳市旺富达电子有限公司
SHEN ZHEN WFD ELECTRONICS CO., LTD

PART NO.	244301XXXNXXRUX0X
TITLE:	1.27PF 1xNPin H4.3 90°