

HSF RoHS FILE NO:E362810


SPECIFICATIONS
Rated Current:1.5AMP
Contact Resistance:20mΩ Max
Withstand Voltage:400V AC/DC
Insulation Resistance:800MΩ Min
Operation Temperature:−40°c to +105°c


Contact Material:Brass
Contact Plating:Au or Sn Over Ni
Insulator Material:Polyester(UL94V−0)
Standard: PA6T
Max.Processing Temp: 230°C for 30−60 seconds
(260°C for 10 seconds)



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE± 0.05)







Ordering Information

3220 XX S XX X B D02 X 0X

- XX — No.of Pins: 6−−64
- XX — Contact Plating: G0:Gold Flash; G1:1U" Gold; G2:1.5U" Gold; G3:2U" Gold; G4:3U" Gold; G5:5U" Gold; S0:Gold Flash/Tin; SN:Tin
- X — Insulator Material Option: A=BK−PBT; C=BK−PA6T; D=BK−PA46; E=BK−PA9T; F=BK−LCP
- X — Packing: 0=PE Bag; A=Tray; T=Tube; P=Tube+Cap

Dimension antitheses list		
ITEM	PB	PC
Alternate	XXXmm	XXXmm

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2021.11.18	NEW DRAWING	

OPERATION		DRAW	Liu Miao	21.11.18	SCALE	FIT
X.X	±0.30				UNIT	mm
X.XX	±0.20	CHECK			SIZE	A4
X.XXX	±0.10				SHEET	1/1
Angle	±3°	APPROVE			PROJ.	
DIM	TOL					

WFD 深圳市旺富达电子有限公司
CONN SHEN ZHEN WFD ELECTRONICS CO., LTD

PART NO.	3220XXSXXXBD02X0X
TITLE:	2.0Box Header Npin H5.65 180°