
HSF RoHS


FILE NO :E362810

SPECIFICATIONS
Rated Current:1.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:500V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°C to +105°C

Contact Material:Phosphor Bronze
Contact Plating:Au Over Ni
Insulator Material:Polyester(UL94V−0)
Standard: PA9T
Max.Processing Temp: 230°C for 30−60 seconds
(260°C for 10 seconds)




Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)




Ordering Information

2443 02 XX X N XX S O X 01

- XX — No.of Pins: 2*2~2*50
- X — Insulator Material Option:
  A=BK−PBT
  B=BK−PA66
  C=BK−PA6T
  D=BK−PA46
  E=BK−PA9T
  F=BK−LCP
- XX — Contact Plating:
  G0:Gold Flash
  G1:3U" Gold
  G2:5U" Gold
  G3:10U" Gold
  G4:15U" Gold
  G5:30U" Gold
  S0:Gold Flash/Tin
  SN:Tin
- X — Packing:
  T=Tube
  P=Tube+Cap
  R=Reel+Cap
  M=Reel+Mylar





REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2018.08.06	NEW DRAWING	

OPERATION		DRAW	Liu Miao	18.08.06
X.X	±0.30			
X.XX	±0.20	CHECK		
X.XXX	±0.10			
Angle	±3°	APPROVE		
DIM	TOL			

SCALE	FIT
UNIT	mm
SIZE	A4
SHEET	1/1
PROJ.	

WFD CONN 深圳市旺富达电子有限公司
SHEN ZHEN WFD ELECTRONICS CO., LTD

PART NO.	244302XXXNXXSOX01
TITLE:	1.27PF 2xNPin H4.3 180° O Type