

HSF RoHS FILE NO :E362810


SPECIFICATIONS
Rated Current:1.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:500V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°c to +105°c


Contact Material:Phosphor Bronze
Contact Plating:Au Over Ni
Insulator Material:Polyester(UL94V−0)
Standard: PA6T
Max.Processing Temp: 230°C for 30−60 seconds
(260°C for 10 seconds)



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)







Ordering Information

2435 02 XX X N XX M U X 01

- 2435 02 XX: No.of Pins 02~50
- X: Insulator Material Option
  - C=BK−PA6T
  - E=BK−PA9T
  - F=BK−LCP
- N: Contact Plating
  - G1:Gold Flash
  - G2:1.5U" Gold
  - G3:2U" Gold
  - G4:3U" Gold
  - G5:5U" Gold
  - G6:10U" Gold
  - SN:Tin
- XX: Packing
  - T=Tube
  - R=Reel
  - M=Reel+Mylar
- M U X 01

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2018.03.20	NEW DRAWING	

OPERATION		DRAW	Liu Miao	18.03.20	SCALE	FIT
X.X	±0.30				UNIT	mm
X.XX	±0.20	CHECK			SIZE	A4
X.XXX	±0.10				SHEET	1/1
Angle	±3°	APPROVE			PROJ.	
DIM	TOL					

WFD CONN 深圳市旺富达电子有限公司
SHEN ZHEN WFD ELECTRONICS CO., LTD

PART NO.	243502XXXNXXMUX01
TITLE:	1.27PF 2xNPin H3.45 W4.83 SMT