

HSF RoHS FILE NO :E362810

SPECIFICATIONS
Rated Current:1.5AMP
Contact Resistance:20mΩ Max
Withstand Voltage:400V AC/DC
Insulation Resistance:800MΩ Min
Operation Temperature:−40°c to +105°c

Contact Material:Brass
Contact Plating:Au or Sn Over Ni
Insulator Material:Polyester(UL94V−0)
Standard: PA6T
Max.Processing Temp: 230°C for 30−60 seconds
(260°C for 10 seconds)




Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)




Ordering Information

3220 XX M XX X B K00 X 0X

- XX: No.of Pins 6−−64
- XX: Contact Plating
  G0:Gold Flash
  G1:1U" Gold
  G2:1.5U" Gold
  G3:2U" Gold
  G4:3U" Gold
  G5:5U" Gold
  G6:10U" Gold
  G7:15U" Gold
  S0:Gold Flash/Tin
  SN:Tin
- X: Insulator Material Option
  C=BK−PA6T
  D=BK−PA46
  E=BK−PA9T
  F=BK−LCP
- X: Packing
  A=Tray
  T=Tube
  P=Tube+Cap
  R=Reel+Cap





REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2016.05.21	NEW DRAWING	

OPERATION		DRAW	Liu Miao	16.05.21
X.X	±0.30			
X.XX	±0.20	CHECK		
X.XXX	±0.10			
Angle	±3°	APPROVE		
DIM	TOL			

SCALE	FIT
UNIT	mm
SIZE	A4
SHEET	1/1
PROJ.	

WFD 深圳市旺富达电子有限公司
CONN SHEN ZHEN WFD ELECTRONICS CO., LTD

PART NO.	3220XXMXXXBK00X0X
TITLE:	2.0Box Header Npin H5.7mm SMT 带外柱