
HSF RoHS


FILE NO :E362810


SPECIFICATIONS
Rated Current:3.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:1000V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°c to +105°c

Contact Material:Brass
Contact Plating:Au or Sn Over Ni
Insulator Material:Polyester(UL94V−0)
Standard: PA6T
Max.Processing Temp: 230°C for 30−60 seconds
(260°C for 10 seconds)



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)







Ordering Information


2271 02 XX X X XX M O X 0X

No.of Pins Per Row 2~40	Insulator Material Option A=BK−PBT B=BK−PA66 C=BK−PA6T D=BK−PA46 E=BK−PA9T F=BK−LCP	Post W=With Post N=W/O Post	Contact Plating G1:Gold Flash G3:2U" Gold G4:3U" Gold G5:5U" Gold G6:10U" Gold S0:Gold Flash/Tin SN:Tin	Packing T=Tube P=Tube+Cap R=Reel+Cap M=Reel+Mylar	





W= With Post



N= W/O Post

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2012.09.25	NEW DRAWING	

OPERATION		DRAW	Liu Miao	12.09.25	SCALE	FIT
X.X	±0.30				UNIT	mm
X.XX	±0.20	CHECK			SIZE	A4
X.XXX	±0.10				SHEET	1/1
Angle	±3°	APPROVE			PROJ.	
DIM	TOL					

WFD CONN 深圳市旺富达电子有限公司
SHEN ZHEN WFD ELECTRONICS CO., LTD

PART NO.	227102XXXXXXMOX0X
TITLE:	2.54PF H7.1mm 2xNpin SMT 0−Type