

HSF RoHS FILE NO :E362810

SPECIFICATIONS
Rated Current:3.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:1000V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°c to +105°c

Contact Material:Brass
Contact Plating:Au or Sn Over Ni
Insulator Material:Polyester(UL94V−0)
Standard: PA6T
Max.Processing Temp: 230°C for 30−60 seconds
(260°C for 10 seconds)




Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)




Ordering Information

3210 XX R XX X B K00 X 0X

- XX — No.of Pins: 6−−64
- XX — Contact Plating:
  - G0:Gold Flash
  - G1:1U" Gold
  - G2:1.5U" Gold
  - G3:2U" Gold
  - G4:3U" Gold
  - G5:5U" Gold
  - G6:10U" Gold
  - G7:15U" Gold
  - S0:Gold Flash/Tin
  - SN:Tin
- X — Insulator Material Option:
  - A=PBT
  - C=PA6T
  - D=PA46
  - E=PA9T
  - F=LCP
- X — Packing:
  - 0=PE Bag
  - A=Tray
  - T=Tube
  - P=Tube+Cap





REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A	2019.10.15	NEW DRAWING	

OPERATION		DRAW	Liu Miao	19.10.15	SCALE	FIT
X.X	±0.30				UNIT	mm
X.XX	±0.20	CHECK			SIZE	A4
X.XXX	±0.10				SHEET	1/1
Angle	±3°	APPROVE			PROJ.	
DIM	TOL					

WFD CONN 深圳市旺富达电子有限公司 SHEN ZHEN WFD ELECTRONICS CO., LTD

PART NO.	3210XXRXXXBK00X0X
TITLE:	2.54mm Box Header H8.8mm 90° 反弯