

HSF RoHS FILE NO :E362810


SPECIFICATIONS
Rated Current:3.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:1000V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°c to +105°c


Contact Material:Brass
Contact Plating:Au or Sn Over Ni
Insulator Material:Polyester(UL94V−0)
Standard: PA6T
Max.Processing Temp: 230°C for 30−60 seconds
(260°C for 10 seconds)

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE± 0.05)









Ordering Information

2285D1 2 XX X N XX M Y X 0X

- XX — No.of Pins Per Row 2−40
- X — Insulator Material Option: C=BK−PA6T; E=BK−PA9T; F=BK−LCP
- XX — Contact Plating: G1:Gold Flash; G3:2U" Gold; G4:3U" Gold; G5:5U" Gold; S0:Gold Flash/Tin; SN:Tin
- X — Packing: 0=PE Bag; A=Tray; T=Tube; P=Tube+Cap; R=Reel+Cap

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2021.12.29	NEW DRAWING	

OPERATION		DRAW	Liu Miao	21.12.29	SCALE	FIT
X.X	±0.30				UNIT	mm
X.XX	±0.20	CHECK			SIZE	A4
X.XXX	±0.10				SHEET	1/1
Angle	±3°	APPROVE			PROJ.	
DIM	TOL					

WFD CONN 深圳市旺富达电子有限公司
SHEN ZHEN WFD ELECTRONICS CO., LTD

PART NO.	2285D12XXXNXXMYX0X
TITLE:	2.54PF H8.5mm+H2.5mm 2xNpin SMT W5.0mm