
SER	DESCRIPTION	CHK DATE



NOTE
1.Material
Plunger: Brass C3604
Barrel: Brass C3604
Spring: SUS 304
2.Plating
Plunger: 3 micro-inch minimum Au over 50~100 micro-inch nickel
Barrel: 3 micro-inch minimum Au over 50~100 micro-inch nickel
3.Electrical
Rated current & voltage: DC 12V; 1A MAX .
Contact resistance: 50 mohm maximum at working height
4.Mechanical
Spring force: 100g±20g at working height
Durability: 10,000 cycles(minimum)
5.RoHS compliant product.
6.Mark * is the key control dimension
7.Pass the salt spray test for 48 hours

名称	零件料号	用量
针头	TH0014-0103	1 PCS
针管	GF6075-0103	1 PCS
弹簧	X	1 PCS

WFDCONN 深圳市旺富达电子有限公司
SHEN ZHEN WFD ELECTRONICS CO., LTD

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X.X ±0.15 X.XX ±0.10 X.XXX ANG. ±2°	APPROVED BY	DATE	TITLE	
	CHECKED BY	DATE	POGO PIN	
	DRAWN BY Liu Miao	DATE 2021/10/23	DOCUMENT NO DN0XX-00X	PAGE 1
UNIT mm	SIZE A4	PART NO PGC-0.5-7.0-1PIN	REV A	SHEET 1/1 SCALE 1:1