
SER	DESCRIPTION	CHK DATE



NOTE
1.Material
Plunger: Brass C3604
Barrel: Brass C3604
Spring: SUS 304
2.Plating
Plunger: 3 micro-inch minimum Au over 50~100 micro-inch nickel
Barrel: 3 micro-inch minimum Au over 50~100 micro-inch nickel
3.Electrical
Rated current & voltage: DC 12V; 1A MAX .
Contact resistance: 50 mohm maximum at working height
4.Mechanical
Spring force: 180g±20% at working height
Durability: 10,000 cycles(minimum)
5.To ensure the best usage,please operate it based on the working height
Based on the engineering drawings,shall not exceed the maximum allowed compression
6.To avoid arcing issue, The adaptor start to power supply after connector mated fully.
7.RoHS standard products

WFD CONN 深圳市旺富达电子有限公司 SHEN ZHEN WFD ELECTRONICS CO., LTD

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X.X ±0.15 X.XX ±0.10 X.XXX ANG. ±2°	APPROVED BY	DATE	TITLE: POGO PIN	
	CHECKED BY	DATE		
	DRAWN BY: LiuMiao	DATE: 2022/05/10	DOCUMENT NO: DNOXX-00X	PAGE: 1
UNIT: mm	SIZE: A4	PART NO: PGC-0.5-12.5-1PIN-01	REV: A	SHEET: 1/1	SCALE: 1:1