




REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE














PCB图仅做参考

Note:
1.Material:
- 1.1 Housing: High temperature thermoplastic with g.f,UL94v-0
- 1.2 Contact: copper alloy,t=0.15mm
- 1.3 Shell: copper alloy,t=0.30mm

2.Specification:
- 2.1 Current rating:1,5PIN 1.8A Max/2,3,4PIN 1A Max.
- 2.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 100 MΩ Min.
- 2.5 Total mating force: 3.57 Kgf Max.
- 2.6 Total unmating force: 1.0 Kgf Min.
- 2.7 Temperature range: -30°C~80°C

外壳材质
1:C2680R-H
7:SUS304R-1/2H

外壳电镀
1:N50u''
2:雾T50u''
3:N+Au1u''(脚)
4:Au1u''

端子电镀 01:Au1u'';02:Au1.5u'';03:Au3u''
05:Au5u'' ;10:Au10u'';15:Au15u'';30:Au30u''

主体颜色 B:黑色

主体材质 1:LCP

端子材质 4:C5191R-EH

PART NO	USB-F06505-SC062	MATERAL:	SEE NOTE
MODEL NO:	XX	FINSH:	SEE NOTE
UNIT: MM	SIZE: A4	COLOR:	SEE NOTE
TOLERANCE UNSPECIFIED		DR:	LIU MIAO
.x	0.15	CHK:	SIMON
.xx	0.10	APP:	DAVID
.xxx	0.05		
Ang.	1°		

WFDCONN 深圳市旺富达电子有限公司 SHEN ZHEN WFD ELECTRONICS CO., LTD

TITLE: MIRCO USB 5S B TYPE 四脚全插(牛角型)短针6.6版无翻边

DWG NO:	A318	REV:	A
SCALE:	5:1	DATE:	2012.05.02